TECHNICAL SPECIFICATIONS OFAGRICULTURAL IMPLEMENTS

8. LAND LEVELLER Front and Rear Blade



GENERAL

1.	Application	For earth moving and land levelling
2.	Working Width	2435 mm
3.	Tractor power	≥ 50 hp

OVERALL DIMENSIONS

4.	Length	900 mm ± 10 mm
5.	Width	2434 mm ± 25 mm
6.	Height	950 mm ± 10 mm
7.	Weight (min.)	300 kg ± 5 kg

MATERIAL SPECIFICATIONS

8.	Main Frame	100x50x5 mm M.S. box
9.	Mast (A-frame)	62x12 mm M.S. flat with M.S. box 50x50x5 mm
10.	Blade body	6 mm formed M.S. sheet, reinforced with M.S. angle 62x6 mm
11.	Cutting edge	150x10 mm, Hardened steel (HRC ≥ 35)
12.	Parking stand	G.I pipe or M.S box

MISCELLANEOUS

13.	Paint	Double coat with primer after surface finish

TECHNICAL SPECIFICATIONS OFAGRICULTURAL IMPLEMENTS

14.	Nuts and bolts	To be tightened with spring washers
15.	Warranty	Free: 1 year for parts and service
		Extended: 5 years for parts supply on payment