TECHNICAL SPECIFICATIONS OFAGRICULTURAL IMPLEMENTS

11. TRACTOR MOUNTED POST HOLE DIGGER



GENERAL

1.	Application	Digging pits for planting
2.	Working depth (min.)	456 mm
3.	Auger size (optional)	228 mm, 300 mm, 456 mm and 600 mm
4.	U.J Shaft	Provided
5.	Depth gauge	Provided
6.	Storage bucket	Provided
7.	Weight (min.)	200 kg ± 5 kg
8.	Tractor power	≥ 50 hp

MATERIAL SPECIFICATIONS

9.	Main Frame	6 mm, M.S box / pipe
10.	Mast (A-frame)	6 mm, M.S box / pipe
11.	Auger	
	Shaft	60 mm OD, M.S pipe, 15 mm wall thickness
	Screw	7 mm M.S sheet
	Cutting edge	12 mm, hardened steel (HRC ≥ 40), replaceable
12.	Gear Box	Steel cast with 3:1 ratio

TECHNICAL SPECIFICATIONS OFAGRICULTURAL IMPLEMENTS

MISCELLANEOUS

13.	Paints	Double coat after primer and surface finish
14.	Nuts & bolts	To be tightened with spring washers
15.	Warranty	Free: 1 year for parts and service
		Extended: 5 years for parts supply on payment