TECHNICAL SPECIFICATIONS OFAGRICULTURAL IMPLEMENTS

30. POTATO DIGGER-CUM-COLLECTOR

POTATO DIGGER-CUM-COLLECTOR



GENERAL AND TECHNICAL

1.	Application	For harvesting and collecting potatoes
2.	Type of machine	Tractor semi-mounted, trailed and PTO and hydraulic driven
3.	Linkage type	Cat-II (1-point hitch drawbar with four (04) transportation tyres
4.	Functions	Digging, shaking and collecting potatoes
5.	Power requirement	≥ 65-hp
6.	Number of rows	01
7.	Power transmission	PTO shaft, V-belt drive PTO speed 540 rpm
8.	First main web width	750 mm
9.	Second main web width	750 mm
10.	First main web sieving area	105 m^2
11.	Second main web sieving area	146 m^2
12.	Separator deviner web width	850 mm
13.	First separator width	900 mm
14.	Second separator width	650 mm
15.	Picking table width	580 mm
16.	Trash web width	280 mm
17.	Tank storage capacity	2000 kg
18.	Unloading height	3300 mm
19.	Transport speed	25 km/h
20.	Origin	Imported

OVERALL DIMENSIONS

21.	Overall length	7900 mm

TECHNICAL SPECIFICATIONS OFAGRICULTURAL IMPLEMENTS

22.	Overall width	3000 mm	
23.	Overall height	3100 mm	
24.	Weight	≥ 3800 kg	
25.	Warranty	Free:	1 year for parts and service
		Extended:	5 years for parts supply on payment